Examiner: G. Dawson

**Listing of the Claims** 

1. (Currently Amended) [[An]] A surgical device for securing tissue comprising:

a first member including a first compression element;

a second member including a second compression element, the second member being in

movable relation with the first member from a first position to a second position, wherein the

first compression element and the second compression element are configured to receive a

retainer therebetween; [[and]]

an elongated insulation sleeve slidably positionable over the second member, wherein

movement of the insulation sleeve is independent of movement of the second member; and

an energy source operably connected to the first compression element.

2. (Original) The surgical device according to claim 1, further including a bias member

biasing the first member and second member into the first position.

3. (Original) The surgical device according to claim 2, wherein the bias member

imparts a compressive force of between about 1 lb. and 20 lbs. on the retainer.

4. (Original) The surgical device according to claim 1, wherein the first compression

element is an acoustic horn.

5. (Original) The surgical device according to claim 4, wherein the energy source

provides ultrasonic energy.

6. (Canceled)

7. (Original) The surgical device according to claim 5, wherein the ultrasonic energy is

provided through an end portion of the acoustic horn.

Examiner: G. Dawson

8. (Original) The surgical device according to claim 1, wherein the energy source provides energy selected from the group consisting of radio frequency (RF) energy, laser energy,

microwave energy, ultrasound energy, and contact heating energy.

9. (Canceled)

10. (Original) The surgical device according to claim 8, wherein the energy source

provides energy through an end portion of the first compression element.

11-13. (Canceled)

14. (Original) The surgical device according to claim 1, wherein the second member is

movable along a linear path relative to the first member.

15. (Original) The surgical device according to claim 14, wherein the second member is

a tubular member including a proximal end and a distal end, the distal end having a gapped

portion with the second compression element being integrated into the gapped portion.

16. (Original) The surgical device according to claim 15, wherein the first member is

positioned through the tubular member, such that the first compression element is in opposing

relation to the second compression element.

17. (Original) The surgical device according to claim 16, wherein the tubular member is

slidable over the first member.

18. (Original) The surgical device according to claim 17, further comprising an actuation

member operably connected to the proximal end of the tubular member, wherein the actuation

member operates to move the tubular member from the first position to the second position.

Examiner: G. Dawson

19. (Original) The surgical device according to claim 18, wherein the actuation member

includes a bias member biasing the tubular member into the first position.

20. (Original) The surgical device according to claim 19, wherein the bias member

imparts a compressive force of between about 1 lb. and 20 lbs. on the retainer interposed between

the first and second compression elements.

21. (Canceled)

22. (Currently Amended) The surgical device according to claim [[21]] 1, wherein the

elongated insulation sleeve is slidable from a first sleeve position to a second sleeve position.

23. (Currently Amended) The surgical device according to claim 22, wherein the

elongated insulation sleeve provides access to the tubular member gapped portion in the first

sleeve position and covers the tubular member gapped portion in the first second sleeve position.

24. (Currently Amended) [[The]] A surgical device according to claim 21, for securing

tissue comprising:

a first member including a first compression element;

a tubular second member including a proximal end and a distal end, the distal end having

a gapped portion with a second compression element being integrated into the gapped portion,

wherein the tubular second member is movable along a linear path relative to the first member

from a first position to a second position, and wherein the first compression element and the

second compression element are configured to receive a retainer therebetween;

an energy source operably connected to the first compression element; and

an elongated insulation sleeve slidably positionable over the tubular member, the

elongated sleeve further [[comprises]] comprising a collar member configured to receive an end

portion of a suture.

Examiner: G. Dawson

25. (Currently Amended) [[The]] A surgical device according to claim 21, further including for securing tissue comprising:

a first member including a first compression element;

a tubular second member including a proximal end and a distal end, the distal end having a gapped portion with a second compression element being integrated into the gapped portion, wherein the tubular second member is movable along a linear path relative to the first member from a first position to a second position, and wherein the first compression element and the second compression element are configured to receive a retainer therebetween;

an energy source operably connected to the first compression element;

an elongated insulation sleeve slidably positionable over the tubular member, wherein the insulation sleeve is slidable from a first sleeve position to a second sleeve position; and a bias member[], [] biasing the elongated sleeve into the first sleeve position.

26-34. (Canceled)

- 35. (Currently Amended) A surgical device for securing tissue comprising:
- a first member including a first compression element;

a tubular member including a gapped portion configured to receive a retainer therein, the gapped portion including an integrated second compression element, wherein the tubular member is slidably <u>positionable</u> over the first member, such that the first compression element is in opposing relation to the second compression element;

an energy source operably connected to the first compression element; and
an elongated insulation sleeve slidably positionable over the tubular member, wherein the
elongated insulation sleeve is slidable from a first sleeve position, covering the gapped portion of
the tubular member, to a second sleeve position, uncovering the gapped portion of the tubular
member, and wherein the sliding of the insulation sleeve is independent of movement of the
tubular member.

Examiner: G. Dawson

36. (Original) The surgical device according to claim 35, wherein the retainer is

interposed between the first and second compression elements.

37. (Original) The surgical device according to claim 36, further comprising an actuation

member operably connected to the tubular member, wherein the actuation member operates to

the move the tubular member from the first position to the second position.

38. (Original) The surgical device according to claim 37, further including a bias

member biasing the tubular member into the first position.

39. (Original) The surgical device according to claim 38, wherein the bias member

imparts a compressive force of between about 1 lb. and 20 lbs. on the retainer interposed between

the first and the second compression elements.

40. (Canceled)

41. (Canceled)

42. (Original) The surgical device according to claim 41, wherein the elongated

insulation sleeve covers the tubular member slotted portion in the first sleeve position.

43. (Currently Amended) [[The]] A surgical device according to claim 41, further

including for securing tissue comprising:

a first member including a first compression element;

a tubular member including a gapped portion configured to receive a retainer therein, the

gapped portion including an integrated second compression element, wherein the tubular member

is slidably positionable over the first member such that the first compression element is in

opposing relation to the second compression element;

an energy source operably connected to the first compression element;

Examiner: G. Dawson

an elongated insulation sleeve slidably positionable over the tubular member from a first

sleeve position to a second sleeve position; and

a bias member[[,]] biasing the elongated insulation sleeve into the first sleeve position.

44. (Currently Amended) [[The]] A surgical device according to claim 41 for securing

tissue comprising:

a first member including a first compression element;

a tubular member including a gapped portion configured to receive a retainer therein, the

gapped portion including an integrated second compression element, wherein the tubular member

is slidably positionable over the first member such that the first compression element is in

opposing relation to the second compression element;

an energy source operably connected to the first compression element; and

an elongated insulation sleeve slidably positionable over the tubular member from a first

sleeve position to a second sleeve position, the elongated sleeve further [[comprises]] comprising

a collar member configured to receive an end portion of a suture.

45. (Currently Amended) The surgical device according to claim [[34]] 35, wherein the

first compression element is an acoustic horn.

46. (Original) The surgical device according to claim 45, wherein the energy source

provides ultrasonic energy.

47. (Canceled)

48. (Currently Amended) A surgical device for securing tissue comprising:

a first member including a first compression element;

a tubular member including a gapped portion configured to receive a retainer therein, the

gapped portion including an integrated second compression element, wherein the tubular member

Examiner: G. Dawson

is slidably positionable over the first member, such that the first compression element is in

opposing relation to the second compression element;

a bias member operably connected to the tubular member, the biasing member biasing the

tubular member into a first position and imparting a compressive force of between about 1 lb.

and 20 lbs. on a retainer interposed between the first compression element and the second

compression element;

an elongated insulation sleeve slidably positionable over the tubular member, wherein the

elongated insulation sleeve is slidable from a first sleeve position, covering the gapped portion of

the tubular member, to a second sleeve position, uncovering the slotted portion of the tubular

member, and wherein the sliding of the insulation sleeve is independent of movement of the

tubular member; and

an ultrasonic energy source operably connected to the first compression element.

49-51. (Canceled)